



技术参数:
 插芯:
 - 插针数: 5+PE
 - 额定电流: 16A
 - 相对地额定电压: 230V
 - 相间额定电压: 400V
 - 额定脉冲电压: 4kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 600V
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: > 500
 插针:
 - 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理:
 · 镀银
 · 镀金
 - 接触电阻: $< 1\text{m}\Omega$
 - 线径范围:
 · 冷压连接: $0.14-2.5\text{mm}^2(26-14 \text{ AWG})$
 · PE连接: $2.5\text{mm}^2(14 \text{ AWG})$
 外壳:
 - 材料:
 · 塑料外壳: 聚碳酸酯
 · 金属外壳: 压铸锌
 - 依据UL 94的阻燃等级:
 · 塑料外壳: V0
 · 塑料外壳: IP67
 · 金属外壳: IP44
 IP67(实现螺栓密封)
 - 附件:
 · 保险延迟针:
 CESM-1.0R/CESM-1.5R/CESM-2.5R
 · 冷压钳:
 TL02G(0.5-4mm²)
 TL02(0.14-0.37mm²)
 · 退针器: TL01
 · 编码元件: CODE-E

Technical specification:
 Insters:
 - No. of contact: 5+PE
 - Rated current: 16A
 - Rated voltage - ground: 230V
 - Rated voltage - conductor: 400V
 - Rated impulse voltage: 4kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 600V
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: > 500
 Contacts:
 - Terminal: crimp terminal
 - Material: copper alloy
 - Surface:
 · Hard-silver plated
 · Hard-gold plated
 - Contact resistance: $< 1\text{m}\Omega$
 - Wire gauge:
 · Crimp terminal: $0.14-2.5\text{mm}^2(26-14 \text{ AWG})$
 · PE contact: $2.5\text{mm}^2(14 \text{ AWG})$
 Hoods/Housings:
 - Material:
 · Plastic hoods/housings: polycarbonate
 · Metal hoods/housings: zinc die-cast
 - Flammability acc.to UL 94: V0
 - Degree of protection, acc.to IEC 60529 for coupled connector:
 · Plastic hoods/housings: IP67
 · Metal hoods/housings: IP44
 IP67(is achieved with seal screw)
 - Accessories:
 · Relay contacts:
 CESM-1.0R/CESM-1.5R/CESM-2.5R
 · Crimp contact tool:
 TL02G(0.5-4mm²)
 TL02(0.14-0.37mm²)
 · Contact removal tool: TL01
 · Coding element: CODE-E

						表面处理 Finish		-		图号 Drawing No.		-		
						材料 Material		-		产品代号 Part Code		HQ-005/0-FC		
标记 Mark	处数 Number	变更描述/Description			签名 Signature	日期 Date					产品料号 Part No.		1300050200001	
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name		-		
绘图 Drawn	BQ LUO	18.10.2010	标准化 Stand.	-	-	1:1	V1.0	14.3g	-					
审核 Checked	P RAO	18.10.2010												
工艺 Process	-	-	批准 Approved	YY LIN	18.10.2010			All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD				